

ECE 2025 Spring 2003
Lab #5: Digital Images: A/D and D/A

Date: 11 – 17-Feb 2003

You should read the Pre-Lab section of the lab and do all the exercises in the Pre-Lab section before your assigned lab time. You **MUST** complete the online Pre-Post-Lab exercise on Web-CT at the beginning of your scheduled lab session. You can use MATLAB and also consult your lab report or any notes you might have, but you cannot discuss the exercises with any other students. You will have approximately 20 minutes at the beginning of your lab session to complete the online Pre-Post-Lab exercise. The Pre-Post-Lab exercise for this lab includes some questions about concepts from the previous Lab report as well as questions on the Pre-Lab section of this lab.

The Warm-up section of each lab must be completed **during your assigned Lab time** and the steps marked *Instructor Verification* must also be signed off **during the lab time**. One of the laboratory instructors must verify the appropriate steps by signing on the **Instructor Verification** line. When you have completed a step that requires verification, simply raise your hand and demonstrate the step to the TA or instructor. After completing the warm-up section, turn in the verification sheet to your TA.

It is only necessary to turn in Section 3 as this week's lab report. More information on the lab report format can be found on Web-CT under the "Information" link. You should **label** the axes of your plots and include a title and Figure number for every plot. Every plot should be referenced by Figure number in your text discussion. In order to make it easy to find all the plots, include each plot *inlined* within your report. For more information on how to include figures and plots from MATLAB to your report file, consult the "Information" link on Web-CT. If you still do not know how to do so, ask your TA.

Forgeries and plagiarism are a violation of the honor code and will be referred to the Dean of Students for disciplinary action. You are allowed to discuss lab exercises with other students and you are allowed to consult old lab reports but the submitted work should be original and it should be your own work.

The lab report for this week will be an **Informal Lab Report**.

The report will be **due during the period 18-Feb to 24-Feb at the start of your lab**.

The objective in this lab is to introduce digital images as a second useful signal type. We will show how the A-to-D sampling and the D-to-A reconstruction processes are carried out for digital images. In particular, we will show a commonly used method of image zooming (reconstruction) that gives "poor" results—a later lab will revisit this issue and do a better job.

1 Pre-Lab

1.1 Digital Images

In this lab we introduce digital images as a signal type for studying the effect of sampling, aliasing and reconstruction. An image can be represented as a function $x(t_1, t_2)$ of two continuous variables representing the horizontal (t_2) and vertical (t_1) coordinates of a point in space.¹ For monochrome images, the signal $x(t_1, t_2)$ would be a scalar function of the two spatial variables, but for color images the function $x(\cdot, \cdot)$

¹The variables t_1 and t_2 do not denote time, they represent spatial dimensions. Thus, their units would be inches or some other unit of length.

would have to be a vector-valued function of the two variables.² Moving images (such as TV) would add a time variable to the two spatial variables.

Monochrome images are displayed using black and white and shades of gray, so they are called *gray-scale* images. In this lab we will consider only sampled gray-scale still images. A sampled gray-scale still image would be represented as a two-dimensional array of numbers of the form

$$x[m, n] = x(mT_1, nT_2) \quad 1 \leq m \leq M, \text{ and } 1 \leq n \leq N$$

where T_1 and T_2 are the sample spacings in the horizontal and vertical directions. Typical values of M and N are 256 or 512; e.g., a 512×512 image which has nearly the same resolution as a standard TV image. In MATLAB we can represent an image as a matrix, so it would consist of M rows and N columns. The matrix entry at (m, n) is the sample value $x[m, n]$ —called a *pixel* (short for picture element).

An important property of light images such as photographs and TV pictures is that their values are always non-negative and finite in magnitude; i.e.,

$$0 \leq x[m, n] \leq X_{\max}$$

This is because light images are formed by measuring the intensity of reflected or emitted light which must always be a positive finite quantity. When stored in a computer or displayed on a monitor, the values of $x[m, n]$ have to be scaled relative to a maximum value X_{\max} . Usually an eight-bit integer representation is used. With 8-bit integers, the maximum value (in the computer) would be $X_{\max} = 2^8 - 1 = 255$, and there would be $2^8 = 256$ gray levels for the display, from 0 to 255.

1.2 Displaying Images

As you will discover, the correct display of an image on a computer monitor can be tricky, especially after some processing has been performed on the image. We have provided the function `show_img.m` in the *SP-First* toolbox to handle most of these problems,³ but it will be helpful if the following points are noted:

1. All image values must be non-negative for the purposes of display. Filtering may introduce negative values, especially if differencing is used (e.g., a high-pass filter).
2. The default format for most gray-scale displays is eight bits, so the pixel values $x[m, n]$ in the image must be converted to integers in the range $0 \leq x[m, n] \leq 255 = 2^8 - 1$.
3. The actual display on the monitor is created with the `show_img` function.⁴ The `show_img` function will handle the color map and the “true” size of the image. The appearance of the image can be altered by running the pixel values through a “color map.” In our case, we want “grayscale display” where all three primary colors (red, green and blue, or RGB) are used equally, creating what is called a “gray map.” In MATLAB the `gray` color map is set up via

```
colormap(gray(256))
```

which gives a 256×3 matrix where all 3 columns are equal. The function `colormap(gray(256))` creates a linear mapping, so that each input pixel amplitude is rendered with a screen intensity proportional to its value (assuming the monitor is calibrated). For our lab experiments, non-linear color mappings would introduce an extra level of complication, so we won't use them.

²For example, an RGB color system needs three values at each spatial location: one for red, one for green and one for blue.

³If you have the MATLAB Image Processing Toolbox, then the function `imshow.m` can be used instead.

⁴If the MATLAB function `imagesc.m` is used to display the image, two features will be missing: (1) the color map may be incorrect because it will not default to gray, and (2) the size of the image will not be a true pixel-for-pixel rendition of the image on the computer screen.



4. When the image values lie outside the range [0,255], or when the image is scaled so that it only occupies a small portion of the range [0,255], the display may have poor quality. In this lab, we will use `show_img.m` to *automatically rescale the image*: This requires a linear mapping of the pixel values:⁵

$$x_s[m, n] = \mu x[m, n] + \beta$$

The scaling constants μ and β can be derived from the min and max values of the image, so that all pixel values are recomputed via:

$$x_s[m, n] = \left\lfloor 255.999 \left(\frac{x[m, n] - x_{\min}}{x_{\max} - x_{\min}} \right) \right\rfloor$$

where $\lfloor x \rfloor$ is the floor function, i.e., the greatest integer less than or equal to x .

1.3 MATLAB Function to Display Images

You can load the images needed for this lab from `*.mat` files, or from `*.png` files. Image files with the extension `*.png` can be read into MATLAB with the `imread` function. Any file with the extension `*.mat` is in MATLAB format and can be loaded via the `load` command. To find some of these files, look for `*.mat` in the *SP-First* toolbox or in the MATLAB directory called `toolbox/matlab/demos`. Some of the image files are named `lenna.mat`, `echart.mat` and `zone.mat`, but there are others within MATLAB's demos. The default size is 256×256 , but alternate versions are available as 512×512 images under names such as `lenna512.mat` and `zone512.mat`. After loading, use the command `whos` to determine the name of the variable that holds the image and its size.

Although MATLAB has several functions for displaying images on the CRT of the computer, we have written a special function `show_img()` for this lab. It is the visual equivalent of `soundsc()`, which we used when listening to speech and tones; i.e., `show_img()` is the "D-to-C" converter for images. This function handles the scaling of the image values and allows you to open up multiple image display windows. Here is the help on `show_img`:

```
function [ph] = show_img(img, figno, scaled, map)
%SHOW_IMG    display an image with possible scaling
% usage:    ph = show_img(img, figno, scaled, map)
%    img = input image
%    figno = figure number to use for the plot
%            if 0, re-use the same figure
%            if omitted a new figure will be opened
% optional args:
%    scaled = 1 (TRUE) to do auto-scale (DEFAULT)
%            not equal to 1 (FALSE) to inhibit scaling
%    map = user-specified color map
%    ph = figure handle returned to caller
%-----
```

Notice that unless the input parameter `figno` is specified, a new figure window will be opened.

1.4 Get Test Images

In order to probe your understanding of image display, do the following simple displays:

- (a) Load and display the 326×426 "lighthouse" image from `lighthouse.png`. This image can be downloaded from Web-CT. The MATLAB command `ww = imread('lighthouse.png')` will put the sampled image into the array `ww`. Use `whos` to check the size and type of `ww` after loading. Notice that the array type for `ww` is `uint8`, so it might be necessary to convert `ww` to double

⁵The MATLAB function `show_img` has an option to perform this scaling while making the image display.



CD-ROM

IMAGE
DATA
FILES



CD-ROM

show_img.m

precision floating-point with the MATLAB command `double`. When you display the image it might be necessary to set the colormap via `colormap(gray(256))`.

- (b) Use the colon operator to extract the 440th row of the “lighthouse” image, and make a plot of that row as a 1-D discrete-time signal.

```
ww440 = ww(440, :);
```

Observe that the range of signal values is between 0 and 255. Which values represent white and which ones black? Can you identify the region where the 440th row crosses the fence? Can you match up a black region between the image and the 1-D plot of the 440th row?

2 Warm-up

The instructor verification sheet may be found at the end of this lab.

2.1 Synthesize a Test Image

In order to probe your understanding of the relationship between MATLAB matrices and image display, you can generate a synthetic image from a mathematical formula.

- (a) Generate a simple test image in which all of the columns are identical by using the following *outer product*:

```
xpix = cos(2*pi/32*(1:256)')*ones(1,256);
```

Display the image and explain the gray-scale pattern that you see. How wide are the bands if measured in number of pixels? How can you predict that width from the formula for `xpix`?

- (b) In the previous part, which data value in `xpix` is represented by white? which one by black?
- (c) Explain how you would produce an image with bands that are vertical. Give the formula that would create a 512×512 image with 4 vertical black bands separated by white bands. Write the MATLAB code to make this image and display it.

Instructor Verification (separate page)

2.2 Printing Multiple Images on One Page

The phrase “what you see is what you get” can be elusive when dealing with images. It is *very tricky* to print images so that the hard copy matches exactly what is on the screen, because there is usually some interpolation being done by the printer or by the program that is handling the images. One way to think about this in signal processing terms is to think of the screen as one kind of D-to-A and the printer as another kind; each one uses a different kind of (D-to-A) reconstruction method to get the continuous-domain (analog) output image that you see.

Furthermore, if you try to put two images of different sizes into subplots of the same MATLAB figure, it won't work because MATLAB wants to force them to be the same size. Therefore, you should display your images in separate MATLAB Figure windows. In order to get a printout with multiple images on one page, use the following procedure:

1. In MATLAB, use `show_img` and `trusize` to put your images into separate figure windows at the correct pixel resolution.
2. Use the Windows program called `PAINT` to assemble the different images onto one page. This program can be found under `Accessories`.

3. For each MATLAB figure window, do `ALT-PRINT-SCREEN` which will copy the active window contents to the clipboard.
4. After each “window capture” in step 3, paste the clipboard contents into `PAINT`.⁶
5. Arrange the images so that you can make a comparison for your lab report.
6. Print the assembled images from `PAINT` to a printer.

2.3 Sampling of Images

Images that are stored in digital form on a computer have to be sampled images because they are stored in an $M \times N$ array (i.e., a matrix). The sampling rate in the two spatial dimensions was chosen at the time the image was digitized (in units of samples per inch if the original was a photograph). For example, the image might have been “sampled” by a scanner where the resolution was chosen to be 300 dpi (dots per inch).⁷ If we want a different sampling rate, we can simulate a *lower* sampling rate by simply throwing away samples in a periodic way. For example, if every other sample is removed, the sampling rate will be halved (in our example, the 300 dpi image would become a 150 dpi image). Usually this is called *sub-sampling* or *down-sampling*.⁸

Down-sampling throws away samples, so it will shrink the size of the image. This is what is done by the following scheme:

$$wp = ww(1:p:end, 1:p:end);$$

when we are downsampling by a factor of p .

- (a) One potential problem with down-sampling is that aliasing might occur. This can be illustrated in a dramatic fashion with the `lighthouse.png` image.

Read in the `lighthouse.png` file with the MATLAB function `imread`. When you check the size of the image, you’ll find that it is not square. Now down-sample the `lighthouse` image by a factor of 2. What is the size of the down-sampled image? Notice the aliasing in the down-sampled image, which is surprising since no new values are being created by the down-sampling process. Describe how the aliasing appears visually.⁹ Which parts of the image show the aliasing effects most dramatically? Explain why the aliasing is happening by thinking about high frequencies in the image.

Instructor Verification (separate page)

3 Lab Exercises: Sampling, Aliasing and Reconstruction

3.1 Reconstruction of Images

When an image has been sampled, we can fill in the missing samples by doing interpolation. For images, this would be analogous to the examples shown in Chapter 4 for sine-wave interpolation which is part of the reconstruction process in a D-to-A converter. We could use a “square pulse” or a “triangular pulse” or other pulse shapes for the reconstruction.

⁶An alternative is to use the free program called IRFANVIEW, which can do image editing and also has screen capture capability. It can be obtained from www.irfanview.com. Other alternatives are Photoshop, or the GIMP at www.gimp.org/win32.

⁷For this example, the sampling periods would be $T_1 = T_2 = 1/300$ inches.

⁸The Sampling Theorem applies to digital images, so there is a *Nyquist Rate* that depends on the maximum *spatial* frequency in the image.

⁹One difficulty with showing aliasing is that we must display the pixels of the image exactly. This almost never happens because most monitors and printers will perform some sort of interpolation to adjust the size of the image to match the resolution of the device. In MATLAB we can override these size changes by using the function `true_size` which is part of the Image Processing Toolbox. In the *SP-First* toolbox, an equivalent function called `true_size.m` is provided.




Figure 1: 2-D Interpolation broken down into row and column operations: the gray dots indicate repeated data values created by a zero-order hold; or, in the case of linear interpolation, they are the interpolated values.

For these reconstruction experiments, use the `pccat.png` image, down-sampled by a factor of p . Use $p = 5$, but write your code so that it would work for any integer value of p . Downsampling should be done in the same manner as in Section 2.3. You will have to read in the image from `pccat.png` using the `imread` function, and store the image into an array named `xx`. Two down-sampled `pccat` images should be created and stored in the variables `xx5` and `xx10`. The objective will be to reconstruct an approximation to the original `pccat` image, which is 892×592 , from the smaller down-sampled images.

- (a) The simplest interpolation would be reconstruction with a square pulse which produces a “zero-order hold.” Here is a method that works for a one-dimensional signal (i.e., one row or one column of the image), assuming that we start with a row vector `xr1`, and the result is the row vector `xr1hold`.

```
xr1 = cos(2*pi*(0:7)/8);
L = length(xr1);
nn = ceil((0.999:1:8*L)/8);    %<-- Round up to the integer part
xr1hold = xr1(nn);
```

Plot the vector `xr1hold` to verify that it is a zero-order hold version derived from `xr1`. Explain what values are contained in the indexing vector `nn`. If `xr1hold` is treated as an interpolated version of `xr1`, then what is the *interpolation factor*? Your lab report should include an explanation for this part; use plots to simplify the explanation.

- (b) Now return to the down-sampled `pccat` image, and process all the columns of `xx5` to fill in the missing points. Use the zero-order hold idea from part (a), but do it for an interpolation factor of 5. Call the result `x5holdcols`. Display `x5holdcols` as an image, and compare it to the downsampled image `xx5`; compare the sizes of the images as well as their content.
- (c) Now process all the rows of `x5holdcols` to fill in the missing points in each row and and call the result `x5hold`. Compare the result (`x5hold`) to the original image `pccat`. Include your code for parts (b) and (c) in the lab report.
- (d) *Linear interpolation* can be done in MATLAB using the `interp1` function (that’s “interp-one”).

When unsure about a command, use `help`.

Its default mode is linear interpolation, which is equivalent to using the `'*linear'` option, but `interp1` can also do other types of polynomial interpolation. Here is an example on a 1-D signal:

```
n1 = 0:7;
xr1 = cos(2*pi*n1/8);
tti = 0:0.1:7;    %<-- locations between the n1 indices
xr1linear = interp1(n1,xr1,tti);    %<-- function is INTERP-ONE
stem(tti,xr1linear)
```

For the example above, what is the interpolation factor when converting `xr1` to `xr1linear`?

- (e) In the case of the `pccat` image, you need to carry out a linear interpolation operation first on the columns and then on the rows of the down-sampled image `xx5`. This can be done with two calls to the `interp1` function, because one call can process all the columns of a matrix.¹⁰ Name the interpolated output image `x5linear`. Include images as well as your code for this part in the lab report.
- (f) Demonstrate that your code is general by processing `xx10`, the downsampled by 10 image. Explain how you wrote the code so that only one line, or one function call has to be changed when going from $p = 5$ to $p = 10$. For this processing, you should only show the final interpolated images.

3.2 Quality of the Interpolation

Comment on the processed images that you created:

- (a) For both cases ($p = 5$ and 10), compare the linear interpolated result to the original image `pccat`. Comment on the visual appearance of the “reconstructed” images versus the original; point out differences and similarities. Describe the degradation that the interpolator causes for $p = 10$. Can the reconstruction (i.e., zooming) process remove the aliasing effects from the down-sampled `pccat` image?
- (b) For both cases ($p = 5$ and 10), compare the quality of the linear interpolation result to the zero-order hold result. Point out regions where they differ and try to justify this difference by estimating the local frequency content. In other words, look for regions of “low-frequency” content and “high-frequency” content and see how the interpolation quality is dependent on this factor.
- (c) Display the `xx5` image (`pccat` downsampled by 5) and be sure that it is “truesize” by using the following:

```
show_img(xx5)
truesize
```

Now expand the display window to full size so that it fills all of the screen. What type of interpolation is MATLAB doing when it expands a window holding an image?

Here are a couple of questions to think about: Are edges low frequency or high frequency features? Are the cat’s whiskers low frequency or high frequency features? Is the background a low frequency or high frequency feature?

Comment: You might use MATLAB’s zooming feature to show details in small patches of the output image. However, be careful because zooming does its own interpolation.

¹⁰Use a matrix transpose in between the interpolation calls. The transpose will turn rows into columns.

3.3 More about Images in MATLAB (Optional)

This section¹¹ is included for those students who might want to relate these MATLAB operations to previous experience with software such as *Photoshop*. There are many image processing functions in MATLAB. For example, try the help command:

```
help images
```

for more information, but keep in mind that the Image Processing Toolbox, which is available in the ECE labs, may not be on your computer.

3.3.1 Zooming in Software

If you have used an image editing program such as the GIMP or Adobe's *Photoshop*, you might have observed how well or how poorly image zooming (i.e., interpolation) is done. For example, if you try to blow up a JPEG file that you've downloaded from the web, the result is usually disappointing. Since MATLAB has the capability to read lots of different formats, you can apply the image zooming via interpolation to any photograph that you can acquire. The MATLAB function for reading JPEG images is `imread()` which would be invoked as follows:

```
xx = imread('foo.jpg','jpeg');
```

Since `imread()` is now part of the the MATLAB core toolbox, you should be able to do this test on your home computer; if not, it can be done in the ECE computer labs.

3.3.2 Warnings

Images obtained from JPEG files might come in many different formats. Two precautions are necessary:

1. If MATLAB loads the image and stores it as 8-bit integers, then MATLAB will use an internal data type called `uint8`. The function `show_img()` cannot handle this format, but there is a conversion function called `double()` that will convert the 8-bit integers to double-precision floating-point for use with filtering and processing programs.

```
yy = double(xx);
```

You can convert back to 8-bit values with the function `uint8()`.

2. If the image is a color photograph, then it is actually composed of three "image planes" and MATLAB will store it as a 3-D array. For example, the result of `whos` for a 545×668 color image would give:

Name	Size	Bytes	Class
xx	545x668x3	1092180	uint8 array

In this case, you should use MATLAB's image display functions such as `imshow()` to see the color image. Or you can convert the color image to gray-scale with the function `rgb2gray()`. For more information on the image processing functions in MATLAB, try help:

```
help images
```

¹¹Optional mean that you don't have to include this in a lab report. This section provided in case you are curious and want to learn more on your own.

Lab #5

ECE-2025

Spring-2003

INSTRUCTOR VERIFICATION PAGE

For each verification, be prepared to explain your answer and respond to other related questions that the lab TA's or professors might ask. Turn this page in at the end of your lab period.

Name: _____

Date of Lab: _____

Part 2.1(c) Create a 512×512 image with 4 vertical black bands separated by white bands. Write the MATLAB code to make this image and display it.

Verified: _____

Date/Time: _____

Part 2.3(a) Downsample the `lighthouse` image to see aliasing. Describe the aliasing, where it occurs in the image, and why it occurs.

Verified: _____

Date/Time: _____